

Power Amplifier

4-8GHz/52dB Gain/52dBm Psat

TLPA4G8G-52-52

TURPA4G8G-5252 is a power amplifier with a typical small signal gain of 52 dB and a normal Psat of 52 dBm across the frequency range of 4 to 8 GHz. The DC power requirement for the amplifier is +28 VDC/3 A. The input port configuration offers coax adapter structure with SMA female and N output port configuration offers coax adapter structure with female .

Features:

- Frequency range: 4-8GHz
- Gain: 52dB Typ
- Output Power Psat: 52dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range		4-8		GHz
小信号增益 Small Signal Gain	50	52		dB
增益平坦度 Gain Flatness		±2	±3	dB
线性输出功率 Output P1dB	50	50.5		dBm
饱和输出功率 Output Psat	51	52		dBm
输入驻波 Input VSWR		1.5	2.0	:1
直流电压 DC Voltage		28	30	V DC
静态电流 Static Current		3		A
饱和电流 Saturation current		20	22	A
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/N Female	
直流偏置 DC Bias	D-SUB-15Pin	
尺寸 Size	270*160*40	mm
重量 Weight	1500	g




绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+30 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



外形图 Outline Drawing: Unit:mm



直流供电接口 DC Supply Connector (DSUB-15 Female):

引脚 Pin	名称 Name	功能 Function
1~3、9、10	VCC	Power supply positive,+26.0-30.0VDC
4~5、11~13	GND	Ground
6	EN	Amplifier Enable: TTL High (5V) (Internally Pulled-High) Amplifier Disable: Short to ground
7、14、15	NC	Not Connected

When the temperature of the case exceeds 75 °C, the power amplifier will

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	°C
存储温度 Non-operating Temperature*	-30		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TURPA4G8G-5252	Power amplifier 4-8GHz,Gain:52dB,Psat:52dBm, +28V DC,Without Heatsink	Rev.1.0
TURPA4G8G-5252 HS	Power amplifier 4-8GHz,Gain:52dB,Psat:52dBm, +28V DC,With Heatsink	Rev.1.0